







HARVEST[®]

TYRES FOR AUSTRALIAN FARMERS

65 SERIES HR45 TUBELESS RADIAL R1 TYRES

-  **Single wire bead** Unique flexible bead bundles have size and shape tailored to each tyre size and load indices.
-  **High ply turn-up** Increased sidewall strength and stability allowing for higher load carrying capacity.
-  **45 degree lugs** Provides long service life, better traction and drawbar pull, reduced fuel consumption, better ride handling and smooth ride on hard soils and road transport.
-  **Premium tread compound** Better suited to Australian soil conditions with longer wear rate and resistance to weather cracking & soil abrasions.
-  **Controlled crown shape** Better flotation, aids with self-cleaning, straight line stability, easier cornering (less steering resistance).
-  **Lug dimensions by tyre size** Each tyre size has unique pattern depth, lug width and number of lugs carefully determined by the application's specific requirements.



Year	
1st Year	Free
2nd Year	Free
3rd Year	Free
4th Year	80%
5th Year	60%
6th Year	40%
7th Year	20%



Size	Max Speed km/h	Type	Design SW ±2%	Design OD ±2%	RC Index	RC (mm) ±2.5%	Tread Depth (mm)	Lug Width (mm)	# of Lugs	Load Index	Approved Rims	Max Pressure (kPa)	Max Pressure (psi)
65 SERIES													
440/65R24	65	T/L	441	1182	37	3465	41	39	18	138A8/135D	W13,W14L,115L,W16L	240	35
480/65R24	65	T/L	479	1235	38	3655	40	40	18	143A8/140D	W14L,W15L,W16L	240	35
440/65R28*	65	T/L	441	1283	39	3850	39	39	20	141A8/138D	W13,W14L,W15L,16L	240	35
480/65R28*	65	T/L	479	1335	40	4055	43	40	20	145A8/142D	W14L,W15L,W16L	240	35
540/65R28*	65	T/L	550	1413	41	4275	42	40	19	152A8/149D	W16L,W18L	240	35
600/65R28*	65	T/L	591	1491	42	4505	45	44	19	157A8/154D	W18L,DD16,DW16A,DD18,DW18A	240	35
540/65R30*	65	T/L	550	1464	42	4505	42	40	20	153D/150D	W16L,W16A,DW16A,W18L	240	35
540/65R34	50	T/L	550	1566	43	4745	46	40	21	152A8/149B	W16L,W16A	240	35
540/65R38	65	T/L	550	1667	44	5000	46	40	23	156A8/153D	W16L,W18L	240	35
600/65R38	65	T/L	591	1491	42	4505	45	40	22	162A8/159D	W18L,DD16,DW16A,DD18,DW18A	240	35
650/65R38*	65	T/L	591	1745	45	5270	58	50	20	162A8/159D	W18L,DW18A,DW20B	200	29
650/65R42	50	T/L	645	1913	47	5850	20	102	30	170A8/168B	DW20A	320	46

*Tyre still under development. Call 1300 761 802 for more information.



PHONE NOW

1300 761 802

Fax 1300 458 353

Australian Tyre Traders Pty Ltd

VICTORIA 23 Sunshine Road, West Footscray. Victoria. 3012
 NEW SOUTH WALES 1/136 Newton Rd, Wetherill Park, New South Wales. 2164
 QUEENSLAND 33 Postle St, Coopers Plains. Queensland. 4108
 NORTH QUEENSLAND 22-26 Jay Street, Bohle. Queensland. 4814
 SOUTH AUSTRALIA 532 Cross Keys Road, Cavan. South Australia. 5094
 TASMANIA 2/7-9 Wilmot St, South Launceston. Tasmania. 7249

sales@tyretraders.com.au | www.tyretraders.com.au