

FLOTATION TYRES



FLOTATION TYRES



The Harvest Flotation Tyre has a larger footprint to reduce soil compaction in both Driven and Free Wheel applications under High Load



FLOTATION - FLOTATION LUG PATTERN OFFERS A LARGE FOOTPRINT FOR REDUCED SOIL COMPACTION

Size	DRIVE WHEEL/ FREE WHEEL	Type	Ply Rating	Pattern	Load Index	Design SW ±2%	Design OD ±2%	Approved Rims	Max Pressure (kPa)	Max Pressure (psi)
400/60-15.5	DW	T/L	14	FLOTATION	132A8	404	874	AG13.00	360	52
400/60-15.5	FW	T/L	14	FLOTATION	145A8	404	874	AG13.00	360	52
400/60-15.5	DW	T/L	18	FLOTATION	151A8	404	874	AG13.00	360	52
400/60-15.5	FW	T/L	18	FLOTATION	155A8	404	874	AG13.00	360	52
500/50-17	DW	T/L	18	FLOTATION	157A8	500	950	16.00	480	70
500/50-17	FW	T/L	18	FLOTATION	160A8	500	950	16.00	480	70
400/60-22.5	DW	T/L	16	FLOTATION	144A8	400	1070	13.00	350	51
400/60-22.5	FW	T/L	16	FLOTATION	156A8	400	1070	13.00	350	51
400/60-22.5	DW	T/L	18	FLOTATION	148A8	400	1070	13.00	430	62
400/60-22.5	FW	T/L	18	FLOTATION	160A8	400	1070	13.00	430	62
500/60-22.5	DW	T/L	16	FLOTATION	151A8	500	1170	16.00	320	46
500/60-22.5	FW	T/L	16	FLOTATION	163A8	500	1170	16.00	320	46
500/60-22.5	DW	T/L	18	FLOTATION	153A8	500	1170	16.00	360	52
500/60-22.5	FW	T/L	18	FLOTATION	165A8	500	1170	16.00	360	52
550/60-22.5	DW	T/L	16	FLOTATION	154A8	550	1238	16.00	280	41
550/60-22.5	FW	T/L	16	FLOTATION	165A8	550	1238	16.00	280	41
600/50-22.5	DW	T/L	16	FLOTATION	153A8	576	1170	20.00	260	38
600/50-22.5	FW	T/L	16	FLOTATION	165A8	576	1170	20.00	260	38
600/50-22.5	DW	T/L	20	FLOTATION	165A8	576	1170	20.00	325	47
600/50-22.5	FW	T/L	20	FLOTATION	176A8	576	1170	20.00	325	47
700/40-22.5	DW	T/L	16	FLOTATION	154A8	710	1180	24.00	220	32
700/40-22.5	FW	T/L	20	FLOTATION	180A8	710	1180	24.00	270	39
600/55-26.5	DW	T/L	16	FLOTATION	159A8	591	1333	20.00	260	38
600/55-26.5	FW	T/L	16	FLOTATION	170A8	591	1333	20.00	260	38
700/50-26.5	DW	T/L	16	FLOTATION	162A8	700	1333	24.00	240	35
700/50-26.5	FW	T/L	16	FLOTATION	174A8	700	1333	24.00	240	35
800/45-26.5	DW	T/L	16	FLOTATION	164A8	800	1333	28.00	220	32
800/45-26.5	FW	T/L	16	FLOTATION	177A8	800	1333	28.00	220	32
650/65-30.5	DW	T/L	16	FLOTATION	167A8	650	1670	20.00	220	32
650/65-30.5	FW	T/L	16	FLOTATION	179A8	650	1670	20.00	220	32
850/50-30.5	DW	T/L	16	FLOTATION	174A8	850	1670	28.00	220	32
850/50-30.5	FW	T/L	16	FLOTATION	186A8	850	1670	28.00	220	32

*DW = Denotes Drive Wheel. FW = Denotes Free Wheel.