

HARVEST HB*R1



HB*R1 TUBE TYPE BIAS PLY AGRICULTURAL R1 TYRES

The HB*R1 Harvest Tyres have been successfully proven in all farm tractor and implement applications throughout Australia. A large selection of sizes are available to ensure perfect fit on a wide range of equipment. The following points outline the key features and benefits of the Harvest HB*R1 Tyres:

-  **5 Year Pro-Rata Guarantee**
-  **Bias Ply Agricultural Tyres**
-  **R1 Traction Drive Pattern**
-  **Approved by Australian Engineers**
-  **Curved Lugs Ensure Thorough Self-Cleaning**
-  **Good Traction In Normal To Moist Soils**



Harvest HB*R1



Year	
1st Year	Free
2nd Year	80%
3rd Year	60%
4th Year	40%
5th Year	20%

REFER PAGE 35 & 36
FOR ALL T&C'S

Size	Type	Ply Rating	Load Index	Design SW ±2%	Design OD ±2%	RC Index	RC (mm) ±2.5%	Approved Rims	Max Pressure (kPa)	Max Pressure (psi)
HARVEST HB*R1 TYRES										
8.3-20	TT	8	102A8	210	950	33	2837	W7	240	35
9.5-20	TT	8	104A8	240	955	33	2808	W7	320	46
8.3-22	TT	8	105A8	225	945	27	2778	W7	240	35
9.5-22	TT	8	107A6	232	1000	34	2985	W7,W8	280	41
8.3-24	TT	8	110A8	211	993	32	2692	W8	300	44
9.5-24	TT	8	112A8	241	1048	35	3120	W8, W8H	280	41
9.5-24	TT	12	115A8	241	1048	35	3120	W8, W8H	360	52
13.6-24	TT	8	120/A8	345	1210	38	3530	W12	200	29
14.9-26	TT	8	125/A8	378	1316	39	3850	W13,	180	26
11.2-28	TT	8	117A8	284	1210	38	3655	W10, W10H	200	29
12.4-28	TT	8	119A8	315	1260	-	3708	W11	220	32
13.6-28	TT	8	122A8	345	1311	39	3850	W12	200	29
18.4-28	TT	8	134A8	467	1501	42	4505	DW16A, W16L	140	20
18.4-28	TT	12	147A8	467	1501	42	4505	DW16A, W16L	200	29
14.9-30	TT	10	131A8	378	1418	41	4275	W13, DW13A	220	32
16.9-30	TT	10	136A8	429	1485	42	4505	W15L, DW15A	200	29
16.9-34	TT	10	138A8	430	1585	43	4745	W15L, DW15A	200	29
14.9-38	TT	8	131A8	378	1621	43	4745	W13A	180	26
HARVEST IRRIGATOR TYRES										
14.9-24	TT	8	124/A8	378	1265	39	-	W12, W13, DW13A	180	26
11.2-38	TT	6	113A8	284	1459	41	-	W10	180	26