

IMPLEMENT TYRES



IMPLEMENT AGRICULTURAL TYRES

The Harvest Tyres HB Implement range has been designed to withstand the harshest of weather conditions in one of the driest farming continents in the world, Australia.



IMPLEMENT **IMPLEMENT 1** **IMPLEMENT 2** **IMPLEMENT 3** **SANDGRIP** **HB46**

 Implement	High flotation with less compaction and more grip
 Implement 1	Implement pattern design with excellent flotation characteristics
 Implement 2	Low section height design, open notch rib tread pattern suitable for agricultural implements
 Implement 3	Industrial pattern that provides excellent grip in all soil types
 Sandgrip	Sandgrip design provides flotation with low soil compaction
 HB46	HB46 has overlapping lugs and low profile design for excellent traction and flotation

Size	Type	Ply Rating	Pattern	Load Index	Design SW ±2%	Design OD ±2%	Approved Rims	Max Pressure (kPa)	Max Pressure (psi)
4.00-12	TT	4	HI - RIB	56A8	112	535	2.50C,3.00D	300	44
9.00-13	TT	6	SANDGRIP	109A8	240	775	6.00F,600G SDC	225	33
9.5L15	TT	12	IMPLEMENT 1	121B	241	762	8LB	450	65
11L15	TT	12	IMPLEMENT 1	121B	274	777	8LB,10LB	360	52
12.5L15	TT	12	IMPLEMENT 1	126A8	318	823	10LB	360	52
10.0/75-15.3	T/L	14	IMPLEMENT 2	130A8	274	760	9.00	470	68
11.5/80-15.3	T/L	14	IMPLEMENT 2	139A8	290	845	9.00	430	62
12.5/80-15.3	T/L	14	IMPLEMENT 2	143A8	307	889	9.00	430	62
12.5-16SL	T/L	12	IMPLEMENT 1	130A8	294	848	10.00	275	40
14L16.1	T/L	10	TRI - RIB	123A8	356	986	16.1XW14C, 16.1XW11CH	300	44
16.5L16.1	T/L	10	IMPLEMENT 1	129A8	419	1072	16.1XW14C, 16.1 XW14CH	240	35
21.5L16.1	T/L	16	IMPLEMENT 1	130A8	318	1130	10.00	275	40
15.0/55-17	T/L	18	IMPLEMENT	149A8	391	850	13.00	420	60
385/65-22.5	T/L	16	HB46	158A8	389	1072	11.75, 12.25 - 22.5	500	73